

## IMPERIA – Technical Data

IMPERIA is an elegant and innovative aniline leather, tanned using a natural by-product of corn and completely free from chrome and metals. The leather is produced in Italy from carefully selected European bull hides, ensuring full traceability and a strong focus on sustainability.

The flat grain combined with the leather’s breathable properties gives IMPERIA a refined, natural appearance and exceptional seating comfort. The surface feels soft and pleasant, and over time the leather develops a beautiful patina that enhances its exclusive character.

IMPERIA is the ideal choice for projects where comfort, aesthetics, and environmental considerations are equally important. The leather is particularly well suited for upholstery of sofas and chairs as well as for furnishing exclusive environments and classic design furniture.

The collection is available in 6 beautiful, classic colours that support a timeless and elegant design universe.

### Note

Aniline leather is an untreated, highly natural leather where colour variations may occur and all natural markings are visible and form part of its character.

It is extremely soft and breathable with high comfort, but has no protective surface.

Extra care is recommended for this type of leather, as it is highly sensitive to stains, sunlight, and wear.

For more detailed information, please visit our website: <https://ca-mo.com/en/laedertype/anilin-laeder/>

---

### Product Information

- **Leather type:** Aniline leather
- **Application:** Upholstery of sofas and chairs as well as exclusive interior projects
- **Average hide size:** approx. 4.8 m<sup>2</sup>
- **Thickness:** 1.3 – 1.5 mm
- **Raw material:** European bull hides
- **Tanning:** Corn-tanned, chrome- and metal-free
- **Environment:** Produced without the use of PCP and CFC and complies with the REACH declaration

---

**Fire Test** – The article meets the requirements according to:

UNI EN ISO 1021 – 1/2

BS 5852 UK Match & Cigarette Test

BS 5852 Crib 5

California T.B. 117

	Method	Test result
Light fastness	DIN EN ISO 105-B02	2-3
Rubbing fastness, dry, 50 rubbings	DIN EN ISO 11640	≥3
Rubbing fastness, wet, 20 rubbings	DIN EN ISO 11640	≥3
Rubbing fastness, sweat, 50 rubbings	DIN EN ISO 11640	≥3
Tearing strength	DIN EN ISO 3377-1	Min. 20 N
Flexing endurance	DIN EN ISO 5402-1	20.000
Finish Adhesion	DIN EN ISO 11644	Min. 4 N/cm