

SIERRA – Technical Data

SIERRA is a corrected leather with a protective surface that provides a uniform structure and makes it easy to work with across many types of projects. The combination of texture and a wide colour range opens up a wealth of design possibilities and invites creativity in both modern and classic interiors.

The protective finish makes SIERRA highly durable and easy to maintain, while still preserving a calm and harmonious appearance. Its consistent look makes it particularly suitable for furniture and upholstery where a clean and well-executed design is essential.

SIERRA can be used for both soft and firm upholstery and performs equally well in private homes and larger public projects such as libraries, schools, and universities, as well as in hotels, restaurants, and shopping centres where materials are exposed to heavy use and require enhanced durability.

With a colour palette of no less than 44 shades, SIERRA offers great freedom in the design process – whether working with subtle tones or bold contrasts.

Note

Corrected leather has a protective surface that ensures high durability, easy maintenance, and a uniform appearance.

Regular care is recommended to maintain the leather's softness and appearance.

For more detailed information, please visit: <https://ca-mo.com/en/laedertype/korrigeret-laeder/>

Product Information

- **Leather type:** Corrected leather
- **Application:** Furniture upholstery – residential and contract
- **Average hide size:** approx. 5.0 m²
- **Thickness:** 0.9 – 1.1 mm
- **Raw material:** Brazilian hides
- **Tanning:** Chrome tanned
- **Environment:** Produced without the use of PCP and CFC and complies with all limits and standards for Chromium VI as well as the REACH declaration

Fire Test – The article meets the requirements according to:

UNI EN ISO 1021 – 1/2

BS 5852 UK Match & Cigarette Test

California T.B. 117

	Method	Test result
Light fastness	DIN EN ISO 105-B02	≥ 4
Rubbing fastness, dry, 500 rubbings	DIN EN ISO 11640/41	4
Rubbing fastness, wet, 250 rubbings	DIN EN ISO 11640/41	4
Rubbing fastness, perspiration, 80 rubbings	DIN EN ISO 11640/41	4
Adhesion of finish	DIN EN ISO 11644	3 N/cm
Tear strength	DIN EN ISO 3377-2	≥ 40 N
Dry flexing resistance	DIN EN ISO 5402-1	50.000
PH value	DIN EN ISO 4045	≥ 3,2